

VISCOM -

Issue date : 22/07/2014

08314 RI-JET DECO WALL 75 EXTRAPERMANENT WKPE140**Face Material**

Gloss white CAST soft vinyl.

Type	Soft vinyl
Colour and Finish	Gloss white polymeric
Weight	70 g/m ² ±10% ISO-536
Thickness	75 µ ±10% ISO 534-80

Adhesive

Permanent adhesive with excellent adhesion on low energy surfaces (i.e. PP or PE containers). The adhesive has a very high peel adhesion and high cohesion.

Reference	ASP
Type	Acrylic Extra Pemanent
Min. Appl. Temp.	+5°C
Service Temp.	-35°C/+120 °C
Shear	High
Tack	12 N/25mm FINAT FTM9
Final Adhesion	17 N/25mm FINAT FTM2

Liner

Type	PE coated kraft paper
Colour and Finish	White
Weight	140 g/m ² ±10% ISO 536
Thickness	150 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

Applications

Decorative applications for outdoor brick wall and irregular surfaces.

This excellent polymeric can be used for difficult application.

The strong bond ensure a secure and weatherproof finish. Printable with UV and solvent screen-printing, UV offset and solvent and eco-solvent based ink-jet.

This film is available in 1.37 m wide roll.

Printing Methods

Application: Only dry application.

Substrate Preparation: All surfaces to which the material will be applied must be without dust .

Ensure all traces of any contamination and cleaning agents are totally removed prior to application of the material.

The compatibility of lacquers and paints should be tested by the user prior to the application.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

Prodotto Distribuito**FI ORE**
VISUAL COMUNICATION MATERIALSwww.fioretorino.com

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.
Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com

