

All films at one glance

Outdoor durability in years	
	Colour

Memoboard films

Memoboard films

PremiumBlackboard ASLAN BB 910	Blackboard film for liquid chalk and chalk	5	Black
Blackboard PP Dryapply ASLAN BBL 920	PVC free blackboard film for liquid chalk and chalk		Black
Blackboard ASLAN C 61	Blackboard film for chalk	2	Black
Blackboard AntiScratch ASLAN CR 62	Blackboard film especially scratch-resistant, for chalk	2	Black
ClearChalk ASLAN CR 63	Blackboard film transparent, for chalk and ASLAN C-pen	2	Transparent
FerroSoft ASLAN FF 410	Very flexible, magnetically-receptive ferrous film		Anthracite
FerroSoft Print ASLAN FF 480	Flexible, printable, magnetically-receptive ferrous film		White
FerroSoft Whiteboard ASLAN FF 550	Flexible, printable, magnetically-receptive ferrous film with glossy whiteboard finish		White
FerroSoft Whiteboard matt ASLAN FF 490	Flexible, magnetically-receptive ferrous film with matt whiteboard finish		White
FerroSoft Blackboard ASLAN FF 540	Flexible, magnetically-receptive ferrous film with blackboard finish		Black
Whiteboard ASLAN WB 995	Scratch-resistant whiteboard film	5	White
Whiteboard Dryapply ASLAN WBL 995	Scratch-resistant whiteboard film, for easy dry application	5	White
WhiteboardMatt ASLAN WB 975	Scratch-resistant, low-reflection whiteboard film, suitable for projection	5	White
Whiteboard PP Dryapply ASLAN WBL 998	PVC free, scratch-resistant whiteboard film, for easy dry application		White
WhiteboardColour ASLAN WBC 996	Scratch-resistant, coloured whiteboard films	5	6 colours
Clearboard ASLAN CB 90	Scratch-resistant whiteboard film	5	Transparent
ClearboardMatt ASLAN CB 75	Scratch-resistant, low-reflection whiteboard film	5	Transparent
EtchedBoard Dryapply ASLAN EBL 300	Glass decoration film with whiteboard finish		Translucent
RearProjection ASLAN RP 35	Rear projection film for transparent surfaces		White, translucent
RearProjection transparent ASLAN RP 36	Rear projection film for transparent surfaces		Transparent
MagneTack ASLAN MT 400	Self-adhesive magnetic film		White

ASLAN Dryapply technology

Glass decoration films

Etched Dryapply ASLAN EL 300	Translucent film with etched glass look	7	Translucent
PrintEtched Dryapply ASLAN DFL 300	Printable, translucent film with etched glass look	7	Translucent
SilverEtched Dryapply ASLAN EL 302	Translucent film with silvery etched glass look	7	Translucent
PrintSilverEtched Dryapply ASLAN DFL 302	Printable, translucent film with silvery etched glass look	7	Translucent
Dusted Dryapply ASLAN EL 200	Translucent film with dusted glass look	7	Translucent
Milky Dryapply ASLAN EL 210	Translucent film with milk glass look	7	Translucent
PrintMilky Dryapply ASLAN DFL 210	Printable, translucent film with milk glass look	7	Translucent

For universal applications

Etched ASLAN E 300	Translucent film with etched glass look	7	Translucent
SilverEtched ASLAN E 302	Translucent film with silvery etched glass look	7	Translucent
Dusted ASLAN E 200	Translucent film with dusted glass look	7	Translucent
Milky ASLAN E 210	Translucent film with milk glass look	7	Translucent

With decorative designs

Illustra Linen ASLAN IL 350	Transparent PVC-film „Linen“-Design	7	Transparent
Illustra Snow ASLAN IL 351	Transparent PVC-film „Snow“-Design	7	Transparent
Illustra Dot ASLAN IL 352	Transparent PVC-film „Dot“-Design	7	Transparent

Coloured films

PremiumColour ASLAN C 118 Soft	Opaque premium colour films, for long-term use	7	34 colours
EcoColour ASLAN C 114	Universal opaque colour films	3-5	46 colours
FluoColour ASLAN CL 70	Fluorescent films	9 12 months	Red Yellow
GlassColour ASLAN CT 113	Transparent colour films	3-5	25 colours

	Matt	Glossy	Thickness in µm	Film	Permanent	Semi-Permanent	Removable	Dryapply	Indoor/outdoor application	Width in m	Standard length in m	Additional lengths	Fire rating B 1	Fire rating EN 13501-1	Catalogue page
			Film		Adhesive					Dimensions			Fire rating		
	●		130	PVC-film with special coating		●			I/O	1.25	25		●		7
	●		130	PP with special coating		●		●	I/O	1.25	25				7
	●		160	PVC-film		●			I/O	1.25	25				7
	●		130	Embossed PVC-film		●			I/O	1.37	25				7
	●		125	Embossed special-PVC-film		●			I/O	1.37	25				7
	●		410	Polyethylene-based ferrous film	●				I	1.01 1.37	12 9		●		8
	●		480	Polyethylene-based ferrous film with PVC-laminate	●				I	1.01	12				8
		●	550	Polyethylene-based ferrous film with PP-laminate	●				I	1.01 1.37	12 9				8
	●		490	Polyethylene-based ferrous film with PP-laminate	●				I	1.37	9				8
	●		540	Polyethylene-based ferrous film with PP-laminate	●				I	1.25	9				8
		●	150	PVC/PET	●				I/O	1.37	50		●		10
		●	150	PVC/PET		●		●	I/O	1.37	50				10
	●		80	PVC with special coating		●			I/O	1.37	50		●		10
		●	150	PP		●		●	I/O	1.37	50				10
		●	150	PVC/PET with special coating		●			I/O	1.22	24				10
		●	50	PET with special coating	●				I/O	1.37	50		●		10
	●		80	PVC with special coating		●			I/O	1.37	50		●		10
	●		80	PVC with special coating		●		●	I	1.37	25		●		10
		●	90	Special-PVC		●			I	1.35	25	12,5			11
		●	50	Special-PET		●			I	1.35	25	12,5			11
		●	400	Polyethylene based film with strontium- and barium ferrite powder	●				I						
	●		80	PVC, polymeric		●		●	I/O	1.26 1.52	50			●	14
	●		80	PVC, polymeric		●		●	I/O	1.37 1.52	50				14
	●		80	PVC, polymeric		●		●	I/O	1.26 1.52	50			●	14
	●		80	PVC, polymeric		●		●	I/O	1.37 1.52	50				14
	●		80	PVC, polymeric		●		●	I/O	1.26	50			●	14
	●		80	PVC, polymeric		●		●	I/O	1.26 1.52	50			●	14
	●		80	PVC, polymeric		●		●	I/O	1.37	50				14
	●		80	PVC, polymeric		●			I/O	1.26	50				15
	●		80	PVC, polymeric		●			I/O	1.26	50				15
	●		80	PVC, polymeric		●			I/O	1.26	50				15
	●		80	PVC, polymeric		●			I/O	1.26	50				15
		●	80	PVC, polymeric		●		●	I/O	1.37	50			●	17
		●	80	PVC, polymeric		●		●	I/O	1.37	50			●	17
		●	80	PVC, polymeric		●		●	I/O	1.37	50			●	17
	●	●	70	PVC, polymeric		●			I/O	1.25	50				23
	●	●	70	PVC, monomeric		●*			I/O	1.22	50				24
		●	100	PVC with special coating		●			I/O	1.25	25				25
		●	80	PVC, monomeric		●			I/O	1.25	25				25

All films at one glance

Outdoor durability
in years

Colour

Metal effect films

Metal effect

MetalPrint ASLAN CA 30	Printable metal effect films	5	6 effects
MetalLux Print ASLAN SEP 50	Printable, scratch-resistant, matt special effect film	2	Champagne Platinum
MetalEffect Dryapply ASLAN CAL 23	Metal effect films for easy dry application	3-5	Silver Gold polished
MetalEffect ASLAN CA 23	Metal effect films	2 / 3-5*	8 effects
MetalColor ASLAN CA 24	Coloured metal effect films	2	5 effects
MetalShadow ASLAN CA 25	Metal effect films in 4 sleek silver tones	2	4 effects
MirrorEffect AntiScratch ASLAN SE 75	Highly reflective, scratch-resistant mirror effect film	3-5	Silver Gold
MirrorEffect SimplyApply ASLAN SE 76	Highly reflective, scratch-resistant mirror effect film for easy dry application		Silver
MetalLux ASLAN SE 50	Scratch-resistant, matt special effect film	2	Champagne Platinum

PVC free films

PVC free

Blackboard PP Dryapply ASLAN BBL 920	Blackboard film for chalk and liquid chalk		Black
Whiteboard PP Dryapply ASLAN WBL 998	Scratch-resistant whiteboard film, for easy dry application		White
FerroSoft Blackboard ASLAN FF 540	Flexible, magnetically-receptive ferrous film with blackboard finish		Black
FerroSoft Whiteboard ASLAN FF 550	Flexible, magnetically-receptive ferrous film with whiteboard finish		White
EcoSoftTouch ASLAN SL 109	Protective PP-laminate with a precious haptic		Transparent
EcoEtched EasyRemove ASLAN ER 151	Translucent, PVC free film with dusted glass look		Translucent
EcoPlot ASLAN PP 112	Universal opaque colour film	3-5	Black White

For painting and lacquering works

Stencil films

PremiumMask ASLAN 85 K	Stencil film for smooth surfaces		Grey, translucent
PremiumMask HighTack ASLAN 85 G	Stencil film for smooth surfaces, with strong adhesion		Grey, translucent
PaintMask ASLAN S 79	Stencil film for truck curtains and other smooth surfaces		Grey green, translucent
WallMask ASLAN S 41	Stencil film for rough walls and facades		Grey, translucent
For sandblasting works			
Sandblast 600 ASLAN S 62	Sandblasting film for heavy-duty sandblasting on stone		Creme, translucent
Sandblast 330 ASLAN S 64	Sandblasting film for heavy sandblasting on stone		Grey, opaque
Sandblast 230 ASLAN S 66	Sandblasting film for medium-duty sandblasting		White, opaque
Sandblast 180 ASLAN S 68	Sandblasting film for medium-duty sandblasting		Grey, transparent
Sandblast 80 ASLAN S 69	Sandblasting film for light sandblasting on glass		Grey green, transparent

Illuminated signs

Blockout ASLAN W 15	Blockout film – black adhesive side	7	White
Blockout ASLAN W 16	Blockout film – white adhesive side	7	Black
Diffuser ASLAN D 160	Diffusion film for optimal light distribution	7	White, translucent
GlassColour ASLAN CT 113	Transparent coloured films	3-5	25 colours

Double-sided self-adhesive films

Premium MountFilm ASLAN DK 1	Double-sided permanent with low initial tack		Transparent
MountFilm Dryapply ASLAN DK 2	Permant, with low initial tack Semi-permanent for easy dry application		Transparent
MountFilm HighTack ASLAN DK 3	Permant with low initial tack Permanent		Transparent
MountFilm Remove ASLAN DK 4	Permant with low initial tack Removable		Transparent

	Matt	Glossy	Thickness in µm	Film	Permanent	Semi-Permanent	Removable	Dryapply	Indoor/outdoor application	Width in m	Standard length in m	Additional lengths	Fire rating B 1	Fire rating EN 13501-1	Catalogue page
	Film		Adhesive						Dimensions			Fire rating			
	●	●	140	PET/PVC	●				I/O	1.25	25				19
	●		140	PET/PVC					I/O	1.25	25				19
		●	50	PET		●		●	I/O	1.25	25				20
	●	●	50	PET		●			I/O	1.25	25				20
		●	140	PET/PVC		●			I/O	1.22	24				20
		●	140	PET/PVC		●			I/O	1.22	24				20
		●	75	PET		●			I/O	1.25	25			●	20
		●	75	PET			●			1.25	25				20
	●		50	PET		●			I/O	1.25	25				20
	●		130	PP with special coating		●		●	I/O	1.25	25				34
		●	150	PP		●		●	I/O	1.37	50				34
	●		540	Polyethylene-based ferrous film with PP-laminate	●				I	1.25	9				34
		●	550	Polyethylene-based ferrous film with PP-laminate	●				I	1.01 1.37	12 9				34
	●		50	PP	●				I	1.37	50				35
	●		170	PP			●		I	1.37	50				35
	●	●	70	PP		●*			I/O	1.25	50				35
			80	PVC			●			1.25	50				37
			80	PVC			●			1.25	50				37
			80	PVC			●			1.25	50				37
			80	PVC			●			1.25	50	25			38
			600	PVC			●			1.25	10				39
			330	PVC			●			1.25	25				39
			230	PVC			●			1.25	25				39
			180	PVC			●			1.25	25				39
			80	PVC			●			1.25	50				39
		●	130	PVC, polymeric			●		I/O	1.25	25				40
		●	130	PVC, polymeric			●		I/O	1.25	25				40
	●		85	PVC, polymeric		●			I/O	1.35	50	25			40
		●	80	PVC, monomeric		●			I/O	1.25	25				25
			70	PVC, monomeric	●*				I	1.35	25				41
			70	PVC, monomeric	●*			●*	I	1.35	50	25			41
			70	PVC, monomeric	●*				I	1.35	50	25			41
			70	PVC, monomeric	●*		●*		I	1.35	50	25			41

All films at one glance

Outdoor durability in years	
	Colour

Protective laminates

Premium FloorProtect ASLAN MP 300	Slip-resistance certification DIN 51130 and ASTM D	Up to 6 months, depending on mechanical load	Transparent
FloorProtect ASLAN MP 326	Slip-resistance certification DIN 51130 and ASTM D	Up to 6 months, depending on mechanical load	Transparent
AntiGraffiti ASLAN SL 95	Protective laminate with anti-graffiti protective coating, especially scratch-resistant	5	Transparent
PremiumProtect ASLAN SL 17	Protective laminate for long-term outdoor use	7	Transparent
PremiumProtect Matt ASLAN SL 18	Protective laminate for long-term outdoor use	7	Transparent
UltraProtect Plus ASLAN SL 05	Protective laminate, very tough	5	Transparent
UV-PrintProtect ASLAN SL 27	Protective laminate, especially for UV-prints	3	Transparent
UV-PrintProtect Matt ASLAN SL 28	Protective laminate, especially for UV-prints	3	Transparent
EcoSoftTouch ASLAN SL 109	Protective PP-laminate with a precious haptic		Transparent

Mounting film and application tapes

ASLAN TMO	PVC-mounting film with release liner, reusable		Transparent
LowTackTape ASLAN TP 110	Paper tape, low adhesion		White
UniversalTape ASLAN TP 122	Paper tape, medium adhesion		White
HighTackTape ASLAN TP 136	Paper tape, high adhesion		White
FilmicTape ASLAN TF 100	Filmic tape		Transparent

Digital printing films at one glance

Outdoor durability in years*	White, glossy	White, matt	Transparent, glossy	Transparent, matt	
	Colour				

Rough walls

UltraTack transparent ASLAN DFP 06	Extra strong adhesion even on non-polar surfaces, for long-term application	7	●		●		
UltraTack ASLAN DFP 07	Extra strong adhesion even on non-polar surfaces, for long-term application	7	●				
UltraTack matt ASLAN DFP 08	Extra strong adhesion even on non-polar surfaces, for long-term application	7		●			
UltraTack grey ASLAN DFP 07G	Extra strong adhesion even on non-polar surfaces, for long-term application with grey adhesive	7	●				
UltraTack matt grey ASLAN DFP 08G	Extra strong adhesion even on non-polar surfaces, for long-term application with grey adhesive	7		●			
WrapTheHouse ASLAN DFP 45	For rough facades, removable up to 6 months	3*	●				
WrapTheHouse matt ASLAN DFP 55	For rough facades, removable up to 6 months	3*		●			
WrapTheHouse transparent ASLAN DFP 65	For rough facades, removable up to 6 months	3*				●	

Smooth walls

WrapTheFloor ASLAN DFP 47	For tiles and polished natural stone, residue-free removal	*	●				
LifeTime Removable ASLAN DFP 40	For indoor applications, residue-free removal up to 12 months		●				
LifeTime Removable ASLAN DFP 41	For indoor applications, residue-free removal up to 12 months				●		
LifeTime Removable ASLAN DFP 42	For indoor applications, residue-free removal up to 12 months			●			

* For more information, please read the technical data sheet ** Laminated with digital printing films ASLAN DFP 46, ASLAN DFP 47 and ASLAN DFP 49

Wall & facade

Matt	Glossy	Thickness in µm	Film	Permanent	Semi-Permanent	Removable	Dryapply	Slip-resistance certification	Indoor/outdoor application	Width in m	Standard length in m	Additional lengths	Fire rating B 1	Fire rating EN 13501 - 1	Catalogue page
		Film	Adhesive						Dimensions			Fire rating			

●		140	PVC	●				R13	I/O	1.37	25		●**		33
●		125	PVC	●				R9	I/O	1.35	50		●**		33
	●	50	PET with special coating	●					I/O	1.37	50	25	●		33
	●	75	PVC, polymeric	●					I/O	1.37	50				33
●		75	PVC, polymeric	●					I/O	1.37	50				33
	●	150	PVC, polymeric	●					I/O	1.37	50				35
	●	75	PVC, monomeric	●					I/O	1.35	50				33
●		75	PVC, monomeric	●					I/O	1.35	50				33
●		50	PP	●					I	1.37	50				33

		70	PVC			●				1.35	50	25			42
		115	Special paper			●				1.22	100				42
		115	Special paper			●				1.22	100				42
		115	Special paper			●				1.22	100				42
		110	LDPE			●				1.22 1.00	100				42

Unsere Digitaldruckfolien finden Sie ab Seite 26

Thickness in µm	Film	Dimensions in m	Permanent	Semi-Permanent	Removable	Dryapply	Indoor/outdoor application	Solvent, Eco-Solvent, UV curing inks and screen printing	Latex inks	FloorProtect ASLAN MP 326	Premium FloorProtect ASLAN MP 300	Fire rating B 1	Fire rating EN 13501 - 1	Catalogue page
			Adhesive					Printability		Laminating films		Fire rating		

80	PVC, polymeric	50 x 1.37	high tack				I/O	●	●					32
75	PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●		32
75	PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●		32
75	PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●		32
75	PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●		32
80	PVC	25 x 1.37	●*		●*		I/O	●	●					27
80	PVC	25 x 1.37	●*		●*		I/O	●	●					27
80	PVC	25 x 1.37	●*		●*		I/O	●	●					27
150	PET/PVC	25 x 1.37			●		I/O	●	●	●	●		●	27
80	PVC, monomeric	50 x 1.37			●*		I	●	●					27
80	PVC, monomeric	50 x 1.37			●*		I	●	●					27
80	PVC, monomeric	50 x 1.37			●*		I	●	●					27

Digital printing films at one glance

Outdoor durability in years*	White, glossy	White, matt	Transparent, glossy	Transparent, matt	Thickness in µm
	Colour				

Smooth walls							
Wall & facade	UltraTack transparent ASLAN DFP 06 Extra strong adhesion even on non-polar surfaces, for long-term application	7	●		●		80
	UltraTack ASLAN DFP 07 Extra strong adhesion even on non-polar surfaces, for long-term application	7	●				75
	UltraTack matt ASLAN DFP 08 Extra strong adhesion even on non-polar surfaces, for long-term application	7		●			75
	UltraTack grey ASLAN DFP 07G Extra strong adhesion even on non-polar surfaces, for long-term application with grey adhesive	7	●				75
	UltraTack matt grey ASLAN DFP 08G Extra strong adhesion even on non-polar surfaces, for long-term application with grey adhesive	7		●			75
Rough floors							
Floor Graphics	WrapTheStreet ASLAN DFP 46 Ideal for asphalt and pavements	**	●				80
	Print'nGo Street ASLAN DFP 36 Printing, apply, ready! R9-classified	2-3		●			125
Smooth floors							
Floor Graphics	Print'nGo ASLAN DFP 33 Printing, apply, ready! R9-classified			●			125
	Print'nGo ASLAN DFP 43 Printing, apply, ready! R13-classified			●			140
	Print'nGo ASLAN DFP 44 Printing, apply, ready! R13-classified					●	140
	WrapTheFloor ASLAN DFP 47 Ideal for tiles and polished natural stone	**	●				150
Carpet							
	WrapTheCarpet ASLAN DFP 49 For short pile carpets	**	●				150
Glass and transparent, smooth surfaces							
	WindowClear ASLAN DFP 18 Printable film for transparent surfaces	7			●		80
	WindowBlock ASLAN DFP 25 Double sided blackout film	3	●				180
	LifeTime Removable ASLAN DFP 40 For indoor applications, residue-free removal up to 12 months		●				80
	LifeTime Removable ASLAN DFP 41 For indoor applications, residue-free removal up to 12 months				●		80
	LifeTime Removable ASLAN DFP 42 For indoor applications, residue-free removal up to 12 months			●			80
	PrintEtched Dryapply ASLAN DFL 300 Printable, translucent film with etched glass look	7	Translucent				80
	PrintSilverEtched Dryapply ASLAN DFL 302 Printable, translucent film with silvery etched glass look	7	Translucent				80
	PrintMilky Dryapply ASLAN DFL 210 Printable, translucent film with milk glass look	7	Translucent				80
	LightboxPrint Dryapply ASLAN DFL 20 Highly translucent, for an easy dry application	7		●			90
	Illustra Linen ASLAN IL 350 Transparent PVC-film „Linen“-Design	7			●		80
	Illustra Snow ASLAN IL 351 Transparent PVC-film „Snow“-Design	7			●		80
	Illustra Dot ASLAN IL 352 Transparent PVC-film „Dot“-Design	7			●		80
	PrintMetal ASLAN CA 30 Printable metal effect film	5	6 metal effects				140
	MetalLux Print ASLAN SEP 50 Printable, scratch resistant, matt special effect film	2	Champagne Platinum				140
	FerroSoft Print ASLAN FF 480 Flexible, printable, magnetically-receptive ferrous film			●			480
Universal applications on smooth surfaces							
	LifeTime Removable ASLAN DFP 40 For indoor applications, residue-free removal up to 12 months		●				80
	LifeTime Removable ASLAN DFP 41 For indoor applications, residue-free removal up to 12 months				●		80
	LifeTime Removable ASLAN DFP 42 For indoor applications, residue-free removal up to 12 months			●			80
	PrintMetal ASLAN CA 30 Printable metal effect film	5	7 metal effects				140
	UltraTack Plus ASLAN DFP 05 Extra strong adhesion even on non-polar surfaces, for long-term application	2-3	●				80

* For more information, please read the technical data sheet **Protective films page 50

Film	Dimensions in m	Permanent	Semi-Permanent	Removable	Dryapply	Indoor/outdoor application	Solvent, Eco-Solvent, UV curing inks and screen printing	Latex inks	FloorProtect ASLAN MP 326	Premium FloorProtect ASLAN MP 300	Fire rating B 1	Fire rating EN 13501-1	Fire rating DIN EN-13501-1, printed and laminated with ASLAN MP 300 or ASLAN MP 326	Catalogue page
PVC, polymeric	50 x 1.37	high tack				I/O	●	●						32
PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●			32
PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●			32
PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●			32
PVC, polymeric	50 x 1.37	high tack				I/O	●	●			●			32
PVC	25 x 1.37			●*		I/O*	●	●	●	●			●	28
PVC	25 x 1.37			●*		I/O	●	●						28
PVC	25 x 1.37		●			I	●	●			●			28
PVC, polymeric	25 x 1.37		●			I	●	●						28
PVC, polymeric	25 x 1.37		●			I	●	●						28
PET/PVC	25 x 1.37			●		I/O	●	●	●	●			●	28
PET/PVC	25 x 1.37			●		I	●	●	●	●			●	28
PVC, polymeric	50 x 1.37		●			I/O	●	●						30
PVC	25 x 1.37			●		I/O	●	●			●			31
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						30
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						30
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						30
PVC, polymeric	50 x 1.37 1.52		●		●	I/O	●	●						33
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						17
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						17
PVC, polymeric	50 x 1.37		●		●	I/O	●	●						16
PET/PVC	25 x 1.25		●			I/O	●	●						19
PET/PVC	25 x 1.25					I/O	●	●						19
PE/PVC	12 x 1.01	●				I	●	●						8
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PVC, monomeric	50 x 1.37			●*		I	●	●						27
PET/PVC	25 x 1.25	●				I/O	●	●						19
PVC, monomeric	50 x 1.37	●				I/O	●	●						32